

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE August 15, 1999	3. REPORT TYPE AND DATES COVERED Final Report: 5/95 through 5/99
4. TITLE AND SUBTITLE Hydraulic Conductivity Measurement in Unsaturated Soils with a Modified Cone Penetrometer		5. FUNDING NUMBERS DAAH04-95-1-0228	
6. AUTHOR(S) Dr. Molly M. Gribb			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of South Carolina, Office of Sponsored Programs & Research Columbia, SC 29208		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING / MONITORING AGENCY REPORT NUMBER ARO33796.1-EV-YIP	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.			
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) In this project, a new cone penetration test (CPT) method for the determining the hydraulic properties of unsaturated soil was developed. A modified cone penetrometer (cone permeameter) is used to inject water into the soil under constant pressure through a screen and measure movement of the wetting front with tensiometer rings. An inverse methodology is used to analyze the cumulative inflow volume and pressure head readings to obtain estimates of the hydraulic conductivity and soil-moisture retention curves for the soil. To accomplish the inversion, a cone permeameter test is numerically simulated with the radially symmetric form of Richard's equation and the van Genuchten hydraulic conductivity and moisture retention functions. An objective function expressing the differences between flow responses measured with the cone permeameter and those predicted using the numerical model with the parameterized soil hydraulic properties is minimized to obtain the hydraulic parameter estimates. Full-scale tests in a laboratory aquifer and field tests were performed during the course of this study. Excellent agreement between saturated hydraulic conductivity values obtained with the cone permeameter and values from in-situ Guelph permeameter and laboratory falling head tests was obtained. Soil-moisture retention curves were similar to those obtained from multi-step outflow and capillary rise tests.			
14. SUBJECT TERMS vadose zone, soil-water characteristic curves, unsaturated hydraulic conductivity, cone penetration testing		15. NUMBER OF PAGES 14	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev.2-89)
Prescribed by ANSI Std. Z39-18
298-102

TABLE OF CONTENTS

LIST OF FIGURES AND TABLES	2
STATEMENT OF THE PROBLEM STUDIED	3
RESEARCH OBJECTIVES	3
BACKGROUND	4
SUMMARY OF THE MOST IMPORTANT RESULTS	6
ARMY RELEVANCE	10
BIBLIOGRAPHY	10
PARTICIPATING SCIENTIFIC PERSONNEL	11
REPORT OF INVENTIONS	11
LIST OF ALL PUBLICATIONS AND TECHNICAL REPORTS	11

LIST OF FIGURES AND TABLES

Figure 1.	Prototype cone permeameter.	5
Figure 2.	Cone permeameter set-up for laboratory aquifer and field testing.	6
Figure 3.	Cone permeameter set up for field testing.	8
Figure 4.	Observed and simulated responses for cone permeameter Test B at Site 1 in Poinsett State Park.	9
Figure 5.	Soil-moisture retention curves resulting from standard methods and inversion of flow data from five cone permeameter tests at Site 1 in Poinsett State Park. Curves A, C, and D are from analysis of the infiltration part of the experiments, while B and E are from both infiltration and redistribution (dB and dE are the drying branches). Curves CR and MO are from capillary rise and multi-step outflow experiments, respectively.	9
Table 1.	Saturated hydraulic conductivity values obtained via inversion of cone permeameter data and standard test methods (h_0 = supply pressure head value).	10

HYDRAULIC CONDUCTIVITY MEASUREMENT IN UNSATURATED SOILS WITH A MODIFIED CONE PENETROMETER

Final Report ARO Young Investigator Program Army Research Office

Molly M. Gribb, Ph.D., Associate Professor
Department of Civil and Environmental Engineering
300 Main Street, Columbia, South Carolina 29208
Tel: 803-777-6166; Fax: 803-777-0670; E-mail: gribb@sc.edu

STATEMENT OF THE PROBLEM STUDIED

A new in situ method for characterization of unsaturated soil hydraulic properties was studied. Knowledge of these soil properties is necessary for predicting the movement of water and water-borne contaminants from surface and near-surface sources to groundwater, design of bioremediation systems, prediction of infiltration capacity, and determining the susceptibility for landslides and floods. Many existing approaches for measurement of hydraulic properties in unsaturated soils are limited to near-surface application and require augering a borehole, which may result in contaminated soil being brought to the surface. In this project, a new cone penetrometer test (CPT) method for determining the hydraulic properties of unsaturated soils was developed and tested. While CPT methods exist for measurement of the hydraulic conductivity of saturated soil, no methods were previously available for determination of the soil-moisture characteristic curve and hydraulic conductivity function of unsaturated soils. This work is important because CPT methods for site exploration are preferred at contaminated sites. CPT methods do not produce soil cuttings at the surface, and can provide more rapid characterization of the subsurface than traditional methods. Given the potential of this new CPT method for expedited site characterization, this work directly supports the Army's needs improved methods for characterizing and remediating its contaminated sites.

RESEARCH OBJECTIVES

The overall goal of this project was to develop a CPT-based methodology for investigating the fundamental relationships between measurable transient unsaturated flow responses and soil hydraulic parameters. Specific objectives of this work included 1) designing a modified cone penetrometer (called a cone permeameter) to inject water into to subsurface and measure pressure head responses, 2) creating an inverse methodology for estimating hydraulic properties of unsaturated soils from cone permeameter data, 3) demonstrating the performance of a prototype via carefully controlled full-scale laboratory tests, and 4) testing the methodology and instrumentation in the field.

BACKGROUND

The cone permeameter was designed to determine the soil water retention curve, $\theta(h)$, the relationship between the water content and the pressure head of an unsaturated soil, and the unsaturated hydraulic conductivity function of the soil, expressed in terms of pressure head or water content, $K(h)$ or $K(\theta)$. Knowledge of these curves is required for accurate numerical modeling of variably saturated flow. The van Genuchten (1980) analytical functions are commonly used to describe these hydraulic properties:

$$\theta_e = \frac{\theta(h) - \theta_r}{\theta_s - \theta_r} = \frac{1}{(1 + |\alpha h|^n)^m}, \quad h < 0$$

$$\theta_e = 1, \quad h \geq 0 \quad (1)$$

$$K(h) = K_s \theta_e' \left[1 - (1 - \theta_e'^{1/m})^m \right]^2 \quad h < 0$$

$$K(h) = K_s, \quad h \geq 0 \quad (2)$$

where θ_e is the effective water content ($L^3 L^{-3}$), θ_r and θ_s are the residual and saturated water contents ($L^3 L^{-3}$) respectively, α (L^{-1}), n and m ($=1-1/n$) are empirical fitting parameters (-), K_s is the saturated hydraulic conductivity (LT^{-1}) and l is the pore connectivity parameter (-). The pore connectivity parameter, l , is commonly set equal to 0.5 (Mualem, 1976).

To develop a CPT tool and methodology for determining the soil hydraulic properties $K(h)$ and $\theta(h)$ for vadose zone soils, the cone permeameter was designed to inject water into the soil under constant pressure through a screen and to measure movement of the wetting front with tensiometers above the screen (Figure 1) (Leonard, 1997; Gribb et al., 1998). The parameters describing the $K(h)$ and $\theta(h)$ relationships are determined via analysis of cumulative inflow volume and pressure head readings using an inverse solution technique. To accomplish the inversion, a cone permeameter test is numerically simulated with the radially symmetric form of Richards equation and the van Genuchten (1980) functions of $K(h)$ and $\theta(h)$:

$$\frac{\partial \theta}{\partial t} = \frac{1}{r} \frac{\partial}{\partial r} \left[r K \frac{\partial h}{\partial r} \right] + \frac{\partial}{\partial z} \left[K \left(\frac{\partial h}{\partial z} + l \right) \right] \quad (3)$$

Then an objective function, Φ , expressing the differences between flow responses measured with the cone permeameter and those predicted using the numerical model with parameterized soil hydraulic properties, is minimized:

$$\Phi(b, q, p) = \sum_{j=1}^{m_q} v_j \sum_{i=1}^{n_{qj}} w_{i,j} [q_j^*(x, t_i) - q_j(x, t_i, b)]^2 + \sum_{j=1}^{m_p} v_j \sum_{i=1}^{n_{pj}} \bar{w}_{i,j} [p_j^*(\theta_i) - p_j(\theta_i, b)]^2 \quad (4)$$

where the first term on the right side represents deviations between measured and predicted space-time variables (e.g., pressure heads or moisture contents at different locations and/or times, or the cumulative infiltration rate versus time). In this term, m_q is the number of different sets of measurements, and n_{qj} is the number of measurements in a particular measurement set. Specific measurements at time t_i for the j th measurement set at location $x(r, z)$ are represented by $q_j^*(x, t_i)$, $q_j(x, t_i, \mathbf{b})$ are the corresponding model predictions for the vector of optimized parameters \mathbf{b} (e.g., $\theta_r, \theta_s, \alpha^w, \alpha^d, n, K_s$), and v_j and $w_{i,j}$ are weights associated with a particular measurement set or point, respectively. The weighting factor, v_j , is given by the inverse of the number of measurements multiplied by the variance of those observations, and $w_{i,j}$ is equal to 1 in this work. The second term on the right represents differences between independently measured $p_j^*(\theta_i)$ and predicted $p_j(\theta_i, \mathbf{b})$ soil hydraulic properties (e.g., $\theta(h)$, $K(\theta)$ or $K(h)$ data), while the terms m_p , n_{pj} , v_j and $w_{i,j}$ have similar meanings as for the first term, but are now for the soil hydraulic properties. Minimization of the objective function Φ is accomplished by using the Levenberg-Marquardt nonlinear minimization method (Marquardt, 1963), which combines the Newton and steepest descent methods.




Figure 1. Prototype cone permeameter.

SUMMARY OF THE MOST IMPORTANT RESULTS

The project objectives described above were met via a fully integrated numerical and experimental research program. Numerical studies were undertaken to investigate the effects of varying hydraulic soil properties and test conditions on observed flow responses. A fully functional prototype cone permeameter and data acquisition system were designed and fabricated. Full-scale soil tank experiments were performed to assess the validity of the numerical model predictions and the applicability and ease of use of the prototype in sandy soil (Gribb et al., 1998; Kodesova et al., 1998a,b, 1999a; Šimůnek et al., 1999) (Figure 2). Finally, a field demonstration of the prototype was completed (Kodesova et al., 1999b). The information gained on unsaturated flow processes through this work provides the basis for future work with other soil types, and investigations into the effects of soil anisotropy and disturbance due to cone penetration. Specific results include are as follows:

- We modified a standard size cone penetrometer housing to allow injection of water into the subsurface through a screened section at a known pressure and measure the pore water pressure at two locations with tensiometer assemblies (shown in Figure 1). We developed inverse solution methods to predict the soil hydraulic properties from data obtained during transient flow tests and objectives functions of the form shown in Eq. 4 (Gribb et al., 1998; Kodesova et al., 1998b, 1999a).




Figure 2. Cone permeameter set-up for laboratory aquifer and field testing.

- We tested the cone permeameter in a laboratory aquifer and compared the results of inversion to results from standard methods including in situ slug tests, and laboratory constant head permeability, pressure plate, capillary rise and hanging column tests. The cone permeameter results compared favorably with results from the standard methods, suggesting that this tool can be used to estimate $K(h)$ and $\theta(h)$ in sandy soil (Gribb et al., 1998; Kodesova et al., 1998a,b, 1999a).
- We then tested the cone permeameter at three sites in a sandy, relatively homogeneous soil (Figure 3). We compared the inversion results to results from standard methods including falling head, pressure plate, capillary rise, and multi-step outflow laboratory tests and in situ Guelph permeameter tests. The cone permeameter results compared favorably with results from the standard methods, suggesting that this tool can be used to estimate $K(h)$ and $\theta(h)$ in sandy in-situ soils. Figure 4 shows test data (cumulative inflow volume and pressure head readings) and simulated results for a single test. The estimated $\theta(h)$ curves with respect to those obtained using the standard methods are shown in Figure 5, and the saturated hydraulic conductivity values obtained from inversion of test data from one location are shown in Table 1. Excellent agreement between the hydraulic conductivity values was obtained (Kodesova et al., 1999b).
- We analyzed the usability/practicality of the prototype and test method and modified the procedure and equipment accordingly. Analysis of the procedure included the impact of cone permeameter placement (pushed vs. buried) and the impact of the initial soil moisture content on estimates of the soil hydraulic properties. We found that the effect of soil densification caused by direct push was minimal, but resulted in slightly lower values of θ_s and K_s than when the prototype was buried prior to testing (Kodešová, et al., 1998a,b) and that additional inputs of initial soil moisture content are helpful for more precise determination of the hydraulic parameters usually investigated (θ_s , θ_r , α , n , and K_s) (Kodešová, et al., 1998b, 1999a). The equipment modifications included modifying the screen to prevent clogging, improving the method of assembly for the tensiometer sections, and devising a method to insert the permeameter into the soil to minimize disturbance.
- We also examined the impact of varying the number of hydraulic parameters to be estimated and found that optimization of additional parameters (l , the pore connectivity factor, and k^A , an anisotropy factor) improved the fit of measured data (Šimůnek et al., 1999; Kodešová, et al., 1999a). We also showed that we can find the wetting branch of soil hydraulic characteristics from the main wetting part of experiment, as well as simultaneously evaluate the wetting and drying curves via analysis of both wetting and redistribution parts of a cone permeameter test (Šimůnek et al., 1999; Kodešová, et al., 1999a).
- In addition to using this method to predict soil hydraulic properties of unsaturated soils, we examined the feasibility of using the cone permeameter and a simplified analysis method to predict the saturated hydraulic conductivity rapidly, while still in the field (currently, the inverse solution is not suited to analysis in real time). We found that the log-transformation of the steady state inflow rate, Q , and the saturated hydraulic conductivity, K_s , yielded a

linear relationship. Comparison of inverse solution results for K_s from the laboratory aquifer and field tests of the cone permeameter with K_s values predicted with this relationship differed by less than a factor of three. Sensitivity analyses showed that this relationship was significantly influenced by the van Genuchten parameters α and n while, but not by the values of θ_r and θ_s . (Al-Houri, 1999). More work is needed on this topic to determine if a reasonably accurate empirical analysis method can be developed. A rapid assessment technique would increase the general usefulness of the cone permeameter by decreasing the computational effort required to analyze the data when only knowledge of K_s is needed.

- The results of the project show that the cone permeameter method can be used to predict the soil hydraulic properties in sandy soils. We have begun field testing the prototype and analysis method in a loamy soil to test the method in soils with greater fines contents. Confirmatory laboratory and field tests are ongoing.




Figure 3. Cone permeameter set up for field testing.




Figure 4. Observed and simulated responses for cone permeameter Test B at Site 1 in Poinsett State Park (Kodesova et al., 1999b).




Figure 5. Soil-moisture retention curves resulting from standard methods and inversion of flow data from five cone permeameter tests at Site 1 in Poinsett State Park. Curves A, C, and D are from analysis of the infiltration part of the experiments, while B and E are from both infiltration and redistribution (dB and dE are the drying branches). Curves CR and MO are from capillary rise and multi-step outflow experiments, respectively (Kodesova et al., 1999b).

Table 1. Saturated hydraulic conductivity values obtained via inversion of cone permeameter data and standard test methods (h_0 = supply pressure head value).

Test Method	K_s (cm/sec)
Multi-Step Outflow Tests (2 samples)	0.0012 – 0.0027
Guelph Permeameter Tests (6 locations)	0.0025 – 0.0039
Laboratory Falling Head Tests (9 samples)	0.0013 – 0.0044
Cone Permeameter Test A: $h_0 = 30, 50$ cm	0.0016
Cone Permeameter Test B: $h_0 = 30, 50$ cm, & redistribution	0.0016
Cone Permeameter Test C: $h_0 = 30, 50$ cm	0.0011
Cone Permeameter Test D: $h_0 = 21, 108$ cm	0.0036
Cone Permeameter Test E: $h_0 = 21, 80$ cm, & redistribution	0.0010

ARMY RELEVANCE

The products of this research project have the potential to enhance the Army's ability to characterize and remediate contaminated sites. When this technology fully developed, it will have numerous advantages over existing methods for soil hydraulic property measurement. As with other CPT tools, the cone permeameter is minimally intrusive and does not result in the removal of potentially contaminated materials. This feature safeguards the welfare of operating crews and reduces site investigation costs. It is applicable to depths of 30 m or more below ground surface, depending on soil resistance to penetration. Since the analysis is based on transient flow data, time and water requirements are minimized. Finally, the inverse solution approach makes it possible to simultaneously determine the soil-moisture retention and hydraulic conductivity curves in unsaturated soils, something not currently possible with other methods.

BIBLIOGRAPHY

Al-Houri, Z., "A regression method for rapid estimation of saturated hydraulic conductivity from cone permeameter data," Masters thesis, Department of Civil and Environmental Engineering, University of South Carolina, 1999.

Gribb, M. M., J. Šimůnek, and M. F. Leonard, "Use of a cone penetrometer method to determine soil hydraulic properties," *Journal of Geotechnical and Geoenvironmental Engineering*, 124(9), 820-829, 1998.

Kodešová, R., M. M. Gribb, and J. Šimůnek, "A New CPT Method for Estimating Soil Hydraulic Properties," *Proceedings of ISC '98*, Eds. P. K. Robertson and P.W. Mayne, A. A. Balkema, Rotterdam, The Netherlands, Vol. 2, 1421-1425, 1998a.

Kodešová, R., M. M. Gribb and J. Šimůnek, "Estimating soil hydraulic properties from transient cone permeameter data," *Soil Science*, 163(6), 436-453, 1998b.

Kodešová, R., M. M. Gribb and J. Šimůnek, "Use of the cone permeameter method to determine soil hydraulic properties," *Proceedings of the International Workshop on Characterization and Measurement of the Hydraulic Properties of Unsaturated Porous Media*, US Salinity Laboratory, Riverside, California, October 22-24, 1997, in press, 1999a.

Kodešová, R., S. E. Ordway, M. M. Gribb, and J. Šimůnek, "Estimation of soil hydraulic properties with the cone permeameter: field studies," *Soil Science*, in press, 1999b.

Marquardt, D.W., "An algorithm for least-squares estimation of non-linear parameters," *SIAM J. Appl. Math.*, 11: 431-441, 1963.

Šimůnek, J., R. Kodešová, M. M. Gribb, and M. Th. van Genuchten, "Estimating Hysteresis in the Soil Water Retention Function from Cone Permeameter Test Data," *Water Resources Research*, 35(5):1329-1345, 1999.

van Genuchten, M. Th., "A closed-form equation for predicting the hydraulic conductivity of unsaturated soils," *Soil Science Society of America Journal*, 44:892-898, 1980.

PARTICIPATING SCIENTIFIC PERSONNEL

Mike Leonard, 1997, Master of Science

Jean Singleton, 1997, Master of Science

Elizabeth Ott, 1997, Master of Engineering

Sondra Ordway, Master of Engineering, doctoral candidate, 1998 – present

REPORT OF INVENTIONS

U. S. Provisional Patent Application No. 60/042,715, "Modified Cone Penetrometer," with M. F. Leonard, April 1997.

LIST OF ALL PUBLICATIONS AND TECHNICAL REPORTS

Refereed Publications

Benson, C. H. and M. M. Gribb, "Measuring unsaturated hydraulic conductivity in the laboratory and field," In: *Unsaturated Soil Engineering Practice*, S. L. Houston and D. G. Fredlund, eds., Geotechnical Special Publication No. 68, ASCE, New York, NY, 113-168, 1997.

Gribb, M. M., J. Šimůnek, and M. F. Leonard, "Development of a cone penetrometer method to determine soil hydraulic properties," *ASCE Journal of Geotechnical and Geoenvironmental Engineering*, Vol. 124, No. 9, 820-829, 1998.

Gribb, M. M. and G. Sewell, "Application of a general purpose PDE solver for variably-saturated groundwater flow problems," *Ground Water*, Vol. 36, No. 2, 366-372, 1998.

Gribb, M. M., "Parameter estimation for determining hydraulic properties of a fine sand from transient flow measurements," *Water Resources Research*, Vol. 32, No. 7, 1965-1974, 1996.

Kodešová, R., S. E. Ordway, M. M. Gribb, and J. Šimůnek, "Estimation of soil hydraulic properties with the cone permeameter: Field studies," *Soil Science* (in press) 1999.

Kodešová, R., M. M. Gribb and J. Šimůnek, "Estimating soil hydraulic properties from transient cone permeameter data," *Soil Science*, Vol. 163, No. 6, 436-453, 1998.

Leonard, M. F., "Design and laboratory evaluation of a cone permeameter for unsaturated soil hydraulic parameter determination," MS thesis, Univ. of S. Carolina, Columbia, SC, 1997.

Šimůnek J., R. Kodešová, M. M. Gribb and M. Th. van Genuchten, "Estimating hysteresis in soil water retention function from cone permeameter experiments," *Water Resources Research*, Vol. 35, No. 5, 1329-1345, 1999.

Šimůnek, J., M. Th. van Genuchten, M. M. Gribb, and J. W. Hopmans, "Parameter estimation of unsaturated soil hydraulic properties from transient flow processes," *Soil and Tillage Research*, Special issue "State of the art in soil physics and in soil technology of anthropic soils," Vol. 47, No. 1-2, 27-36, 1998.

Singleton, J. E., "Characterization of the hydraulic properties of a laboratory aquifer," MS thesis, Univ. of S. Carolina, Columbia, SC, 1997.

Conference Papers

Gribb, M. M., J. Šimůnek, and M. Th. van Genuchten, "In Situ Estimation of Soil Hydraulic Properties Using Inverse Modeling, *Proceedings of the 1999 Annual ASCE Convention*, Charlotte, NC, Oct. 17-20, 1999, submitted.

Kodešová, R., M. M. Gribb, and J. Šimůnek, "A new CPT method for estimating soil hydraulic properties," *Proceedings of the International Site Characterization Conference*, P. K. Robertson and P.W. Mayne, eds., A. A. Balkema, Rotterdam, Vol. 2, 1421-1425, 1998.

Kodešová, R., M. M. Gribb, and J. Šimůnek, "Use of the cone permeameter method to determine soil hydraulic properties," *Proceedings of the International Workshop on Characterization and Measurement of the Hydraulic Properties of Unsaturated Porous Media*, US Salinity Laboratory

and Dept. of Soil and Environ. Science, UC-Riverside, Riverside, CA, Oct. 22-24, 1997, in press, 1999.

Leonard, M. F., J. E. Singleton, and M. M. Gribb, "Design of a modified cone penetrometer for determination of unsaturated soil hydraulic parameters," *Proceedings of the Joint USAF/USA Contractor Grantee Meeting*, Panama City, FL, 259-263, Feb. 13-17, 1997.

Olsen, R. S., and M. M. Gribb, "Comprehensive presentation of raw CPT data," *Proceedings of the International Symposium on Cone Penetration Testing*, Swedish Geotechnical Society, Linköping, Sweden, Vol. 2, 61-65, 1995.

Šimůnek J., M. M. Gribb, M. Th. van Genuchten, and J. W. Hopmans, "Estimating soil hydraulic properties from field data via inverse modeling," *Proceedings of the Second International Conference on Unsaturated Soils, Unsat '98*, Beijing China, August 27- 30, 515-520, 1998.

Šimůnek, J., M. Th. van Genuchten, M. M. Gribb, and J. W. Hopmans, "Parameter estimation of unsaturated soil hydraulic properties from transient flow processes," *Trans. 16th World Congress of Soil Science*, published on a CD ROM (189-t.pdf), Int. Society of Soil Science, Montpellier, France, 7 pp, Aug. 20-26, 1998.

Singleton, J. E., M. F. Leonard, and M. M. Gribb, "Hydraulic conductivity measurement in unsaturated soils with a modified cone penetrometer," *Proceedings of the Third International Symposium and Exhibition on Environmental Contamination in Central and Eastern Europe*, Warsaw Poland, 660-662, 1996.

Abstracts

Gribb, M. M., and K. J. Bene, "Analysis of a soil leachability model for predicting groundwater contamination from petroleum-contaminated soils," *Proceedings, 1st South Carolina Water and Environment Symposium*, Columbia SC, April 6-7, 1999.

Gribb, M. M., "A modified cone penetrometer for soil hydraulic property determination," *Proceedings of the NSF Civil and Mechanical Systems Workshop for the Advancement and Retention of Underrepresented and Minority Engineering Educators*, Washington DC, Sept. 24-26, 1997.

Kodešová, R., S. E. Ordway, M. M. Gribb and J. Šimůnek, "Estimation of soil hydraulic properties via inverse modeling of lab and field transient flow data sets," *Proceedings of the European Geophysical Society Annual Meeting*, The Hague, Netherlands, April 19-23, 1999.

Kodešová, R., H. Damaskova, and M. M. Gribb, "Validation of HYDRUS-1D for nitrate movement simulation under field conditions," *Proceedings of the Soil Science Society of America Annual Meeting*, p. 168, Baltimore, MD, Oct. 18-22, 1998.

Kodešová, R., M. M. Gribb, S. E. Ordway, and J. Šimůnek, "Hydraulic property estimation with the cone permeameter - field studies," *Proceedings of the Soil Science Society of America Annual Meeting*, p. 330, Baltimore, MD, Oct. 18-22, 1998.

Kodešová, R., S. E. Ordway, M. M. Gribb, and J. Šimůnek, "Hydraulic property estimation with the cone permeameter: field studies," *Proceedings of the International Study Group on Inverse Modeling*, Ravello, Italy, Sept. 1 - 3, 1998 (published on the web at <http://www.geo.uni-bayreuth.de/ISGIM/abs-gribb.html>).

Leonard M. F., M. M. Gribb, and J. Šimůnek, "Cone penetration test method for $K(h)$ determination," *Proceedings of the European Geophysical Society XXII General Assembly*, Vienna, Austria, C261, April 25-27, 1997.

Ordway, S. E., Kodešová, R., M. M. Gribb and J. Šimůnek, "Comparison of several methods for measuring soil hydraulic properties in unsaturated sand," *Proceedings, 1st South Carolina Water and Environment Symposium*, Columbia SC, April 6-7, 1999.

Singleton, J. E., M. F. Leonard, and M. M. Gribb, "A cone penetrometer method for $K(h)$ measurement in situ," *Proceedings of the American Geophysical Union 1997 Spring Meeting*, Baltimore, MD, S161, May 27-30, 1997.